

# Eve

## Emergency LED Luminaire



### Efficient and versatile, Eve is suitable for most emergency lighting applications

- With energy efficient LEDs and reliable lithium iron phosphate battery
- Eve delivers superior light output allowing greater spacing with a D40 classification
- Low 0.5W standby power consumption
- Retrofitting is easy with an adaptor plate to suit older applications included in the box
- Suitable for ceiling recess cut out diameters of 70 mm through to 135 mm
- Energy efficient, long life LEDs 50 000 hours
- Tamper resistant – no dome required
- Pre-wired with flex and plug with remote gear and battery pack
- Manual test switch
- Luminaire 5 year warranty
- Battery 3 year warranty
- Complies to AS/NZS 2293



3W max charge rate



50 000 hours lifetime



Low 0.5W standby power consumption



140 x 17 mm



3 hour emergency duration



D40 spacing classification

#### Ideal for...



Circulation Corridors



Stairwells



Offices and meeting rooms



Reception areas





### Light source information

- Lifetime 50 000 hours
- 3W
- 4x High flux LEDs

### Installation/Mounting

Recessed ceiling mount with 70 mm ceiling hole cut-out. 135 mm with adaptor plate for retrofit

### Material/Finish

White polycarbonate disc with an aluminium heat sink

## Ordering guide

Description	Wt (kg)	SAP Code
EVE LED DISK D40 E2NM	0.35	96294619

### Specification

- Class II electrical
- D40 spacing classification
- Non-maintained emergency luminaire, manual test switch
- AS/NZS 2293
- 3W charge rate, 0.5W standby
- 0°C to 40°C

