

Louis Flex



Production



Warehouses



Exhibition halls



Retail outlets

LED High Bay



Efficient and powerful,
Louis Flex is the expert for
high ceilings

- **FLEX Feature:** Decide on your lumen package directly on site
- 1 size but 2 different FLEX lumen packages available
- **Broad light distribution (120°)** for homogenous illumination
- Including chain lock




Lumen switch
for 2 different
sizes



IP65: Dust
tight and water
resistant




Wide voltage
range from
100 V to 240 V



Ordering guide

Description	SAP Code
LOUIS FLEX LED High Bay, Lumensteps 6000lm, 8700lm, 11500lm & 14000lm	22671973
LOUIS FLEX LED High Bay, Lumensteps 15600lm, 19900lm, 23300lm & 28000lm	22671974

Portfolio overview



Light source information

- Flex: 6000lm | 8700lm | 11500lm | 14000lm | 15600lm | 19900lm | 23300lm | 28000lm
- Efficiency up to 156lm/W
- Lifetime 50000 hours (@L80, Ta 25°C)
- CRI80

Specification

- Class I electrical
- IP65
- IK08
- Wide Voltage Driver 100-240V
- Ambient operating temperature: -20 to +40 °C

Material/Finish

- Body: Polycarbonate (UV stabilised)
- Diffuser: Opal polycarbonate (UV stabilised)
- Bracket: Stainless steel