


# Anna

VARIO FLEX

## Recessed LED Panel




Providing high quality light with low glare and high efficiency.



- **VARIO Feature (Colour Temperature Switch):** The ability to choose your colour temperature on site with the flick of a switch
- **FLEX Feature (Lumen Output Switch):** The flexibility to decide on your lumen package on site with the flick of a switch
- Integrated self-test emergency indicator with the JUST E3 self-test kit
- Energy efficient with 125lm/W
- Gentle, soft and glare free lighting with UGR <19
- Direct replacement for 4x14W T5 or 4x18W T8 fluorescent panels
- Easy, quick and tool-free installation thanks to an integrated connector with a 4-pole push terminal (for up to 2.5 mm<sup>2</sup> wires) enabling loop-in loop-out wiring
- The detachable connector enables first fix wiring and high voltage circuit testing while the luminaire is detached
- JUST – adapt on-site to an emergency version using the Just Emergency PLUG&PLAY kit

	L	W	H1	H2
ANNA Q596	596	596	35	60
ANNA Q622	622	622	35	60
ANNA 1200x300	1196	296	35	60

Dimensions (mm)



Ideal for Schools/universities and office/meeting rooms

### Specification

Electrical class	II
Ambient operating temperature	-20 to +40°C
Driver	ENEC certified
DALI	DALI-2 and SwitchDim – suitable for emergency escape lighting systems acc. to EN 50172

### Installation / Mounting

Mounting	Safety wire included in Q596 and 12x3 versions
Installation	Lay-in installation in T-bar ceiling grids – suitable for surface and plaster board installation (accessories available separately)

### Material / Finish

Frame	Aluminium
Diffuser	TpB rated, PET, opal
Light guide panel	PS
Backplate	Steel sheet

### Light source information

VARIO (Colour temperature switch)	3000 K, 3500 K, 4000 K
FLEX (Lumen switch)	3000 lm (24 W), 3750 lm (30 W), 4000 lm (33 W), 4400 lm (36 W)
Efficiency	up to 125 lm/W
Lifetime	50 000 hours (@L80, Ta 25°C)
MacAdam (Initial)	4

### Controllability (DALI-2)

Dimming level	1-100 %
---------------	---------

### VARIO and FLEX feature

There is no need to worry about lumen packages or colour temperatures anymore – it's always the same product and the adaption to your application can be done directly on site:



Colour temperature switch



Lumen output switch

### Ordering guide

Description	Cat Number
ANNA VARIOFLEX 2 Q596 4400 830/35/40	AN4400VF26X6
ANNA VARIOFLEX 2 12X3 4400 830/35/40	AN4400VF212X3
<b>DALI</b>	
ANNA VARIOFLEX 2 Q596 4400 830/35/40 DALI	AN4400XVF26X6
ANNA VARIOFLEX 2 12X3 4400 830/35/40 DALI	AN4400XVF212X3
<b>Accessories</b>	
TECO ANNA V RECESSED SPRINGS	ANVF2PBSRING
TECO SURFACE MOUNT BOX Q596	ECOSURBOX
TECO SURFACE MOUNT BOX 12X3	ECO12X3SURBOX
JUST E3 PLUG&PLAY KIT SELF TEST LiFePO4	ECOE3TLIFEKIT
JUST E3 PLUG&PLAY KIT MANUAL TEST LiFePO4	ECOE3MLIFEKIT

830–3000K / 835–3500K / 840–4000 K