

Holly

Wall-mounted LED
Outdoor Luminaire



Ideal for:
Building facades and residential

Elegant in appearance, Holly is the perfect match for any wall.



IP65




IK04


- Elegant and timeless design
- 3 different designs (round, square, can)
- Up/downlight versions available to create wallwash effect
- Zero uplight versions available to reduce light pollution
- Special designed back plate provides mounting flexibility
- Fast and easy installation thanks to a well positioned 3 pole terminal block



Can version



Round and square version



Specification

Electrical class	I
Ambient operating temperature	-20 to +40 °C

Installation / Mounting

Mounting



Fast and easy installation thanks to a well positioned 3 pole terminal block

Special designed back plate provides more flexibility in mounting

Material / Finish

Body	Aluminium die-cast RAL7016
Front cover	Clear glass

Light source information

Colour temperature	3000 K
Lumen	250 – 500 lm(8W)
Lifetime	50 000 hours (@L80, Ta 25 °C)

Light output

	Round	Square	Can

*No light pollution, zero uplight

Ordering guide

Description	SAP Code
HOLLY CONE ROUND DOWN IP65 300 830	96633683
HOLLY CONE ROUND UP/DOWN IP65 500 830	96633684
HOLLY CONE SQUARE DOWN IP65 300 830	96633685
HOLLY CONE SQUARE UP/DOWN IP65 500 830	96633686
HOLLY WALL CAN DOWN IP65 250 830	96633687