

# Caro




Offices and meeting rooms



Schools and universities

## Recessed LED Panel



Low glare and calm, Caro is the universal talent for desk space environments

- Microprismatic diffusor for gentle and glare free lighting (<19 UGR)
- Easy, quick and tool-free installation thanks to connector with integrated loop-in / loop-out possibility
- Square 600 as well as rectangular 1200 x 300 and 1200 x 600 available






UGR <19:  
gentle, soft and glare-free lighting for office applications



IP44  
(from below):  
Splash resistant for hassle-free cleaning



Wide voltage range from 100 V to 240 V



### Material/Finish

- Material: Aluminium, white (RAL 9003)
- Diffusor and Lightguideplate: PS
- Backplate: Steel sheet





### Ordering guide

Description	SAP Code
CARO Panel, 596x596mm, 3750lm, CCT 840	22671964
CARO Panel, 1200x300mm, 3750lm, CCT 840	22671965
CARO Panel, 1200x600mm, 5000lm, CCT 840	22671966
<b>Accessories</b>	
Spare Driver CARO Q596 + 12x3	22671967
Spare Driver CARO 12x6	22671968
3h Emergency PLUG&PLAY*	22672006
Surface Mount Box for CARO Panel, 596x596mm	96635585
Surface Mount Box for CARO Panel, 1200x300mm	96635572
Surface Mount Box for CARO Panel, 1200x600mm	96635587
Recessed mount Box for CARO Panel, 596x596mm	96634443

\*230V

### Portfolio Overview



### Light source information

- 596x596 and 1200x300: 3750 Lumen
- 1200x600: 5000 Lumen
- Efficiency up to 110lm/W
- 30 000 hours rated life (@L80, Ta 25°C)
- 4000K
- CRI 80
- MacAdam (initial): 4 step

### Specification

- Class II electrical
- IP44 (from below), IP20 from above
- IK03
- Ambient operating temperature: -20 to +40°C
- Lay-in installation in T-bar ceiling grids
- Surface Mount Box available as accessory
- Wide Voltage: 100 V - 240 V